

Pressure washers



Model	DP2300	MDI2900-L
Engine	6.5 hp 4-Stroke OHV Air Cooled	
Displacement	98 cm ³	196 cm ³
Starting System	Recoil	Recoil
Pressure	2175 psi	2900 psi
Delivery	6L/min	11.3 L/min
Hose Length	6 m (20 ft.)	10 m (33 ft.)
Nozzle Quantity	4	5
Dimensions: L / W / H	43 x 36 x 47 cm (17 x 14 x 19 in.)	52 x 72 x 93 cm (21 x 28 x 37 in.)
Dry Weight	16 kg (35 lb)	40 kg (88 lb)



The Ducar Series of fine power generators is characterized by advanced design, compact structure, reliable performance, easy start, low fuel consumption and quiet operation. Ducar offers a complete line of gasoline generators from 1 kW to 9 kW for commercial and consumer applications.

The Ducar Series of power generators is covered by a one-year limited warranty.

They are the best choice for the environmentally conscious user. In fact, all of Ducar's engines have been certified by the EPA (*Environment Protection Agency, USA*). They also meet CSA certification. We are proud to provide you with a safe, reliable and durable power equipment.

Distributed by

 www.mticanada.ca



Your dealer:



Generators



Water pump



Pressure washer

Water pump



Model	D510
Pump Type	Centrifugal
Suction Port Diameter	25 mm (1 in.)
Discharge Port Diameter	25 mm (1 in.)
Total Head	10 m (33 ft.)
Suction Head	6 m (20 ft.)
Flow	85 L/min
Maximum Power Output	1.8 kW
Engine Type	Four-Stroke Single cylinder
Horsepower	2.5 HP
Displacement	98 cm ³
Starting System	Recoil
Fuel Tank Capacity	1.4 L (0.37 gal)
Continuous Working Time	2 hours
Dimensions: L / W / H	39 x 34 x 40 cm (15 x 12 x 16 po)
Dry Weight	11 kg (24 lb)

Generators



Model	DF 1200H	DF 3000H	DFY3000H	DFD 6500H	DFY 6500H	DF 9000H	DFD9000HF
Generator Type	Brushless	Brush Type		Brush Type		Brush Type	Brush Type
Frequency	60 Hz	60 Hz		60 Hz		60 Hz	60 Hz
Maximum AC Output	1200 W	3000 W		6500 W		9000 W	9000 W
Maximum Rated AC Output	900 W	2800 W		5500 W		7500 W	7500 W
AC Voltage	120 V	120 / 240 V		120 / 240 V		120 / 240 V	120 / 240 V
DC Voltage	12 V / 8.3 A	12 V / 8.3 A		12 V / 8.3 A		12 V / 8.3 A	12 V / 8.3 A
Automatic Voltage Regulator	—	—		Standard		Standard	Standard
Engine Type	Four-Stroke, Air-Cooled	Four-Stroke, Air-Cooled		Four-Stroke, Air-Cooled		Four-Stroke, Air-Cooled	Four-Stroke, Air-Cooled
Displacement	98 cm ³	196 cm ³		389 cm ³		420 cm ³	420 cm ³
Horsepower	2.5 HP / 3600 RPM	6,5 HP / 3600 RPM		13 HP / 3600 RPM		15 HP / 3600 RPM	15 HP / 3600 RPM
Starting System	Recoil	Recoil	Remote starter	Electric, Recoil	Remote starter	Electric, Recoil	Electric, Recoil
Fuel Tank Capacity	4.5 L / 1.2 gal	15 L / 4 gal		25 L / 6.6 gal		30 L / 8.0 gal	30 L / 8.0 gal
Oil Tank Capacity	0.4 L / 0.1 gal	0.6L / 0.2 gal		1.1 L / 0.3 gal		1.1 L / 0.3 gal	1.1 L / 0.3 gal
Approx. Running Time	8.5 hours	9 hours		7.5 hours		6 hours	6 hours
Noise Level	65 dB	69 dB		74 dB		77 dB	77 dB
Low Oil Level Alert System	Standard	Standard		Standard		Standard	Standard
Transport Wheels	—	—		Standard		Standard	Standard
Dimensions: L x W x H	44 X 36 X 45 cm (17 X 14 x 17.7 in.)	62 x 46 x 47 cm (24 x 18x 18.5 in.)		83 x 56 x 59 cm (32 x 22 x 23 in.)		83 x 56 x 59 cm (32 x 22 x 23 in.)	83 x 60 x 60 cm (32 x 24 x 24 in.)
Dry Weight	26 kg (57 lb)	45 kg (99 lb)		83 kg (183 lb)		90 kg (198 lb)	90 kg (198 lb)