

Designation Model #	Sno-Tek 24 920402	Classic 24 920025	Compact 20 920026	Compact 24 920027	Deluxe 24 921045	Deluxe 28 921046	Deluxe 28 SHO 921048
STAGE TYPE	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage
ENGINE DISPLACEMENT (CC's)	208cc	208cc	223cc	223cc	254cc	254cc	306cc Gen 3
TORQUE RATING	9.5 ft/lbs	9.5 ft/lbs	10 ft/lbs	10 ft/lbs	12.5 ft/lbs	12.5 ft/lbs	15 ft/lbs
ENGINE BRAND	Sno-Tek	Ariens AX	Ariens AX	Ariens AX	Ariens AX	Ariens AX	Ariens AX
STARTING SYSTEM	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil
CLEARING WIDTH	24 in (60.1 cm)	24 in (60.1 cm)	20 in (50.8 cm)	24 in (60.1 cm)	24 in (60.1 cm)	28 in (71.2 cm)	28 in (71.2 cm)
HOUSING HEIGHT	20 in (50.8 cm)	20 in (50.8 cm)	20 in (50.8 cm)	20 in (50.8 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)
THROWING DISTANCE	3 ft - 40 ft (9-12.2 m)	3 ft - 40 ft (9-12.2 m)			3 ft - 50 ft (9 - 15.2 m)	3 ft - 50 ft (9 - 15.2 m)	3 ft - 55 ft
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°	200°	200°
CHUTE ROTATION	2.5x Quick Turn	2.5x Quick Turn	2.5x Quick Turn	2.5x Quick Turn	2.5x Ice Drill	2.5x Ice Drill	2.5x Ice Drill
CHUTE CONSTRUCTION	Polymer	Steel	Steel	Steel	Steel	Steel	Steel
DEFLECTOR CONTROL	Remote	Remote	Remote	Remote	Remote	Remote	Remote
DASH TYPE	Sno-Tek Dash	Sno-Tek Dash	Compact Ariens	Compact Ariens	Compact Ariens	Compact Ariens	Compact Ariens
FRAME SIZE	Small	Small	Small	Small	Large	Large	Large
HANDLEBAR	Regular Tubular Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar
TIRE SIZE	13 in x 4 in (33 x 10 cm)	13 in x 4 in (33 x 10 cm)	15 in x 4 in (38 x 13 cm)	15 in x 4 in (38 x 13 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)
TREAD PATTERN	Polar Trac	Polar Trac	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread
AXLE SYSTEM	Pin Lock	Pin Lock	Pin Lock	Pin Lock	Auto-Turn	Auto-Turn	Auto-Turn
FUEL TANK CAPACITY	1.5 qt (1.4L)	1.5 qt (1.4L)	1.5 qt (1.4L)	1.5 qt (1.4L)	2.9qt (2.7L)	3.2qt (3.0L)	3.2qt (3.0L)
DRIVE TYPE	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic
SPEEDS: FORWARD AND REV	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse
GEAR CASE	Aluminum	Aluminum	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
GEAR CASE WARRANTY	2yr Consumer, 90 day Commercial		5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial
IMPELLER PROFILE	Steel 3 Blade	Steel 3 Blade	Steel 3 Blade	Steel 3 Blade	Steel 3 Blade	Steel 3 Blade	High Speed Steel 3 Blade
IMPELLER DIAMETER	12 in (30.5 cm)	12 in (30.5 cm)	12 in (30.5 cm)	12 in (30.5 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)
AUGER DIAMETER	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	11 in (27.9 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)
AUGER TYPE	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated
SKID SHOES	Sno-Tek Reversible		Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible
SCRAPER BAR							
PRODUCT WARRANTY	2yr Consumer, 90 day Commercial		3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial
FEATURES AT A GLANCE							
HALOGEN HEADLIGHT	No	No	Standard	Standard	Standard	Standard	Standard
REFLECTIVE DECALS	No	No	No	No	Optional	Optional	Optional
HANDWARMERS	No	No	Optional	Optional	Optional	Optional	Optional
REMOTE DEFLECTOR CONTROL	Standard	Standard	Standard	Standard	Standard	Standard	Standard
ELECTRIC START	Standard	Standard	Standard	Standard	Standard	Standard	Standard
DRIFT CUTTERS	Optional	Optional	Optional	Optional	Optional	Optional	Optional
TRACK DRIVE	No	No	No	No	Optional	Optional	Optional
ONE HAND INTERLOCK	Standard	Standard	Standard	Standard	Standard	Standard	Standard
PACKAGE DIMENSIONS							
LENGTH	44.5 in (113.03 cm)	48 in (121.92 cm)	44.5 in (113.03 cm)	44.5 in (113.03 cm)	51.5 in (130.81 cm)	51.5 in (130.81 cm)	51.5 in (130.81 cm)
WIDTH	27 in (68.58 cm)	27.5 in (68.58 cm)	27 in (68.58 cm)	27 in (68.58 cm)	32 in (81.28 cm)	32 in (81.28 cm)	32 in (81.28 cm)
HEIGHT	34.25 in (86.9 cm)	35 in (88.9 cm)	34.25 in (86.9 cm)	34.25 in (86.9 cm)	35 in (88.9 cm)	35 in (88.9 cm)	35 in (88.9 cm)
DRY WEIGHT	204 lbs (92.53 kg)	200 lbs (90.72 kg)	200 lbs (90.72 kg)	212 lbs (96.16 kg)	245 lbs (111.13 kg)	255 lbs (115.67 kg)	260 lbs (117.93 kg)
ASSEMBLED DIMENSIONS							
LENGTH	51.9 in (131.8 cm)		53.3 in (135.4 cm)	53.3 in (135.4 cm)	58.6 in (148.8 cm)	58.6 in (148.8 cm)	58.6 in (148.8 cm)
WIDTH	43.3 in (110 cm)		44 in (111.8 cm)	44 in (111.8 cm)	45.3 in (115.1 cm)	45.3 in (115.1 cm)	45.3 in (115.1 cm)
HEIGHT	26.4 in (67.1 cm)		22.4 in (56.9 cm)	26.4 in (67.1 cm)	26.4 in (67.1 cm)	29.9 in (75.9 cm)	29.9 in (75.9 cm)
DRY WEIGHT	180 lbs (81.6 kg)		181.1 lbs (82.1 kg)	183.1 lbs (83.1 kg)	245.5 lbs (114.4 kg)	249.8 lbs (113.3 kg)	267.5 lbs (121.3 kg)
AVAILABLE ACCESSORIES	Drift cutter kit, tire chains, composite skid shoes, steel skid shoes, front weight kit, Sno-Thro cab, Sno-Thro cover		Handwarmer kit, tire chains, front weight kit, Sno-Thro cab, Sno-Thro cover, composite skid shoes, drift cutter kit	Handwarmer kit, tire chains, front weight kit, Sno-Thro cab, Sno-Thro cover, composite skid shoes, drift cutter kit	Handwarmer kit, tire chains, track drive conversion kit, front weight kit, drift cutter kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover	Handwarmer kit, tire chains, track drive conversion kit, front weight kit, drift cutter kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover	Handwarmer kit, tire chains, track drive conversion kit, front weight kit, drift cutter kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover



ARIENS

Distribué par / Distributed by :

MTI
CANADA

MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télé. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

Designation Model #	Deluxe 30 921047	Deluxe 30 EFI 921049	Platinum 24 SHO 921050	Platinum 24 SHO EFI 921053	Platinum 30 SHO 921051	Professional 28 926065	Professional Hydro 28 EFI 926068	
STAGE TYPE	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage	
ENGINE DISPLACEMENT (CC's)	306cc Gen 3		369cc Gen 3		414cc Gen 3	420cc	420cc	
TORQUE RATING	15 ft/lbs	15 ft/lbs	17 ft/lbs	17 ft/lbs	20 ft/lbs	21 ft/lbs	21 ft/lbs	
ENGINE BRAND	Ariens AX	Ariens AX	Ariens AX	Ariens AX	Ariens AX	Ariens Polar Force by Briggs & Stratton	Ariens AX	
STARTING SYSTEM	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	
CLEARING WIDTH	30 in (76.2 cm)	30 in (76.2 cm)	24 in (60.1 cm)	24 in (60.1 cm)	30 in (76.2 cm)	28 in (71.2 cm)	28 in (71.2 cm)	
HOUSING HEIGHT	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	23.5 in (59.7 cm)	23.5 in (59.7 cm)	
THROWING DISTANCE	3 ft - 50 ft (.9 - 15.2 m)	3 ft - 50 ft (.9 - 15.2 m)	3 ft - 55 ft	3 ft - 55 ft	3 ft - 55 ft	3 ft - 60 ft	3 ft - 60 ft	
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°	200°	200°	
CHUTE ROTATION	2.5x Ice Drill	2.5x Ice Drill	Quick Turn	Quick Turn	Quick Turn	Quick Turn	Quick Turn	
CHUTE CONSTRUCTION	Steel	Steel	Steel	Steel	Steel	Steel	Steel	
DEFLECTOR CONTROL	Remote	Remote	Remote	Remote	Remote	Remote	Remote	
DASH TYPE	Large Ariens	Large Ariens	Large Ariens	Large Ariens	Large Ariens	Large Ariens	Large Ariens	
FRAME SIZE	Large	Large	Large	Large	Large	Large	Large	
HANDLEBAR	Regular Tubular Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar	Commercial Grade Handlebar	Commercial Grade Handlebar	
TIRE SIZE	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	
TREAD PATTERN	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	
AXLE SYSTEM	Auto-Turn	Auto-Turn	Auto-Turn	Auto-Turn	Auto-Turn	Auto-Turn	Auto-Turn	
FUEL TANK CAPACITY	3.2qt (3.0L)	3.2qt (3.0L)	3.2qt (3.0L)	3.2qt (3.0L)	3.2qt (3.0L)	5.9qt (5.6L)	5.9qt (5.6L)	
DRIVE TYPE	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Hydrostatic	
SPEEDS: FORWARD AND REV	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	6 Forward / 2 Reverse	Variable	
GEAR CASE	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	
GEAR CASE WARRANTY	5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 5yr Commercial	5yr Consumer, 5yr Commercial	
IMPELLER PROFILE	Steel 3 Blade	Steel 3 Blade	High Speed Steel 3 Blade	High Speed Steel 3 Blade	High Speed Steel 3 Blade	Steel 3 Blade	Steel 3 Blade	
IMPELLER DIAMETER	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	
AUGER DIAMETER	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	16 in (40.6 cm)	16 in (40.6 cm)	
AUGER TYPE	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	
SKID SHOES	Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible	Commercial Skids	Commercial Skids	
SCRAPER BAR								
PRODUCT WARRANTY	3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 1yr Commercial	3yr Consumer, 1yr Commercial	
FEATURES AT A GLANCE								
HALOGEN HEADLIGHT	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
REFLECTIVE DECALS	Optional	Optional	Standard	Standard	Standard	Optional	Standard	
HANDWARMERS	Standard	Standard	Standard	Standard	Standard	Standard	Optional	
REMOTE DEFLECTOR CONTROL	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
ELECTRIC START	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
DRIFT CUTTERS	Optional	Optional	Optional	Optional	Optional	Standard	Standard	
TRACK DRIVE	Optional	Optional	Optional	Optional	Optional	Optional	Standard	
ONE HAND INTERLOCK	Standard	Standard	Standard	Standard	Standard	Standard	Optional	
							Standard	
PACKAGE DIMENSIONS								
LENGTH	51.5 in (130.81 cm)		51.5 in (130.81 cm)		51.5 in (130.81 cm)	45.5 in (115.57 cm)	45.5 in (115.57 cm)	
WIDTH	32 in (81.28 cm)		32 in (81.28 cm)		32 in (81.28 cm)	33 in (83.82 cm)	33 in (83.82 cm)	
HEIGHT	35 in (88.9 cm)		35 in (88.9 cm)		35 in (88.9 cm)	39.25 in (99.7 cm)	39.25 in (99.7 cm)	
DRY WEIGHT	300 lbs (136.08 kg)		280 lbs (127.01 kg)		280 lbs (127.01 kg)	315 lbs (142.88 kg)	340 lbs (154.22 kg)	
ASSEMBLED DIMENSIONS								
LENGTH	58.3 in (148.1 cm)		58.3 in (148.1 cm)		58.3 in (148.1 cm)	60.3 in (153.2 cm)	60.3 in (153.2 cm)	
WIDTH	45.5 in (115.6 cm)		45.9 in (116.6 cm)		45.9 in (116.6 cm)	46.6 in (118.4 cm)	46.6 in (118.4 cm)	
HEIGHT	32.4 in (82.3 cm)		26.4 in (67.1 cm)		32.4 in (82.3 cm)	30.2 in (76.7 cm)	30.2 in (76.7 cm)	
DRY WEIGHT	275.6 lbs (125 kg)		286 lbs (129.7 kg)		293.8 lbs (133.3 kg)	339.1 lbs (153.8 kg)	352 lbs (159.7 kg)	
AVAILABLE ACCESSORIES	Tire chains, track drive conversion kit, front weight kit, drift cutter kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover		Tire chains, track drive conversion kit, front weight kit, drift cutter kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover		Tire chains, track drive conversion kit, front weight kit, drift cutter kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover		Tire chains, track drive conversion kit, front weight kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover	



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télé. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

Designation Model #	Professional 32 926071	Professional Hydro 36 EFI 926070	Compact Track 24 920022	Platinum SHO Track 28 921052	Professional Hydro BWT 28 926060	Professional Hydro BWT 32 926069
STAGE TYPE	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage
ENGINE DISPLACEMENT (CC's)	420cc	420cc	208cc	369cc	420cc	420cc
TORQUE RATING	21 ft/lbs	21 ft/lbs	9.5 ft/lbs	17 ft/lbs	21 ft/lbs	21 ft/lbs
ENGINE BRAND	Ariens Polar Force by Briggs & Stratton	Ariens AX	Ariens AX	Ariens AX	Ariens Polar Force by Briggs & Stratton	Ariens Polar Force by Briggs & Stratton
STARTING SYSTEM	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil
CLEARING WIDTH	32 in (81.3 cm)	36 in (91.4 cm)	24 in (60.1 cm)	28 in (71.2 cm)	28 in (71.2 cm)	32 in (81.3 cm)
HOUSING HEIGHT	23.5 in (59.7 cm)	23.5 in (59.7 cm)	20 in (50.8 cm)	21 in (53.3 cm)	23.5 in (59.7 cm)	23.5 in (59.7 cm)
THROWING DISTANCE	3 ft - 60 ft	3 ft - 60 ft	3 ft - 40 ft (9-12.2 m)	3 ft - 55 ft	3 ft - 60 ft	3 ft - 60 ft
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°	200°
CHUTE ROTATION	Quick Turn	Quick Turn	2.5x Quick Turn	Quick Turn	Quick Turn	Quick Turn
CHUTE CONSTRUCTION	Steel	Steel	Steel	Steel	Steel	Steel
DEFLECTOR CONTROL	Remote	Remote	Remote	Remote	Remote	Remote
DASH TYPE	Large Ariens	Large Ariens	Compact Ariens	Large Ariens	Large Ariens	Large Ariens
FRAME SIZE	Large	Large	Small	Large	Large	Large
HANDLEBAR	Commercial Grade Handlebar	Commercial Grade Handlebar	Regular Tubular Handlebar	Regular Tubular Handlebar	Commercial Grade Handlebar	Commercial Grade
TIRE SIZE	16 in x 6.5 in (41 x 17 cm)	16 in x 6.5 in (41 x 17 cm)	5.5" Wide Track	5.5"W	5.5"W	5.5"W
TREAD PATTERN	Directional Snow Tread	Directional Snow Tread	Directional Snow Track	Directional Snow Track	Directional Snow Track	Directional Snow
AXLE SYSTEM	Auto-Turn	Auto-Turn	Solid Locked	Auto-Turn	Auto-Turn	Auto-Turn
FUEL TANK CAPACITY	5.9qt (5.6L)	5.9qt (5.6L)	2.9qt (2.7L)	3.2qt (3.0L)	5.9qt (5.6L)	5.9qt (5.6L)
DRIVE TYPE	Disc-O-Matic	Hydrostatic	Disc-O-Matic	Disc-O-Matic	Hydrostatic	Hydrostatic
SPEEDS: FORWARD AND REV	6 Forward / 2 Reverse	Variable	6 Forward/ 2 Reverse	6 Forward/ 2 Reverse	Variable	Variable
GEAR CASE	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
GEAR CASE WARRANTY	5yr Consumer, 5yr Commercial	5yr Consumer, 5yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 1yr Commercial	5yr Consumer, 5yr Commercial	5yr Consumer, 5yr Commercial
IMPELLER PROFILE	Steel 3 Blade	Steel 3 Blade	Steel 3 Blade	High Speed Steel 3 Blade	Steel 3 Blade	Steel 3 Blade
IMPELLER DIAMETER	14 in (35.6 cm)	14 in (35.6 cm)	12 in (30.5 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)
AUGER DIAMETER	16 in (40.6 cm)	16 in (40.6 cm)	11 in (27.9 cm)	14 in (35.6 cm)	16 in (40.6 cm)	16 in (40.6 cm)
AUGER TYPE	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated
SKID SHOES	Commercial Skids	Commercial Skids	Steel Reversible	Steel Reversible	Commercial Skids	Commercial Skids
SCRAPER BAR						
PRODUCT WARRANTY	3yr Consumer, 1yr Commercial	3yr Consumer, 1yr Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 90 day Commercial	3yr Consumer, 1yr Commercial	3yr Consumer, 1yr Commercial
FEATURES AT A GLANCE						
HALOGEN HEADLIGHT	Standard		Standard	Standard	Standard	Standard
REFLECTIVE DECALS	Optional	Standard	Optional	Standard	Optional	Optional
HANDWARMERS	Standard	Optional	Optional	Standard	Standard	Standard
REMOTE DEFLECTOR CONTROL	Standard	Standard	Standard	Standard	Standard	Standard
ELECTRIC START	Standard	Standard	Standard	Standard	Standard	Standard
DRIFT CUTTERS	Standard	Standard	Optional	Optional	Standard	Standard
TRACK DRIVE	Optional	Standard	Standard	Standard	Standard	Standard
ONE HAND INTERLOCK	Standard	Optional	Standard	Standard	Standard	Standard
PACKAGE DIMENSIONS						
LENGTH	53.5 in (135.89 cm)	51.75 in (131.45 cm)	44.5 in (113.03 cm)	51.5 in (130.81 cm)	45.5 in (115.57 cm)	45.5 in (115.57 cm)
WIDTH	32.25 in (81.92 cm)	40.5 in (102.87 cm)	27 in (68.58 cm)	32 in (81.28 cm)	33 (83.82 cm)	41 in (104.14 cm)
HEIGHT	39.25 in (99.7 cm)	39.25 in (99.7 cm)	34.5 in (87.63 cm)	35 in (88.9 cm)	39.25 in (99.7 cm)	41 in (104.14 cm)
DRY WEIGHT	331 lbs (150.14 kg)	396 lbs (179.62 kg)	249 lbs (112.94 kg)	280 lbs (127.01 kg)	360 lbs (163.29 kg)	385 lb (174.63 kg)
ASSEMBLED DIMENSIONS						
LENGTH	60.3 in (153.2 cm)	60.3 in (153.2 cm)	53.3 in (135.4 cm)	58.5 in (148.6 cm)	60.6 in (153.9 cm)	60.6 in (153.9 cm)
WIDTH	46.6 in (118.4 cm)	46.6 in (118.4 cm)	43.4 in (110.2 cm)	45.3 in (115.1 cm)	45.9 in (116.6 cm)	45.9 in (116.6 cm)
HEIGHT	34.2 in (86.9 cm)	38.2 in (97 cm)	26.4 in (67.1 cm)	29.9 in (75.9 cm)	30.2 in (76.7 cm)	30.2 in (76.7 cm)
DRY WEIGHT	333.6 lbs (151.3 kg)	353 lbs (160.1 kg)	220 lbs (99.8 kg)	306.3 lbs (138.9 kg)	348.7 lbs (158.2 kg)	348.7 lbs (158.2 kg)
AVAILABLE ACCESSORIES						
	Tire chains, track drive conversion kit, front weight kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover	Tire chains, track drive conversion kit, front weight kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover	Handwarmer kit, drift cutter kit, front weight kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover	Drift cutter kit, front weight kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover		

Front weight kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover

Front weight kit, composite skid shoes, Sno-Thro cab, Sno-Thro cover



ARIENS

Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télé. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

Designation Model #	**Ariens Path Pro				Ariens Professional	Ariens Professional
	136E 938034	Ariens Path Pro 938031	Ariens Path Pro 938032	Ariens Path Pro 938033	21 SSR 938024	21 SSRC 938025
STAGE TYPE	Single-Stage	Single-Stage	Single-Stage	Single-Stage	Single-Stage	Single-Stage
ENGINE DISPLACEMENT (CC's)	136cc	208cc	208cc	208cc	208cc	208cc
TORQUE RATING	7.0 ft-lbs	9.5 ft-lbs	9.5 ft-lbs	9.5 ft-lbs	9.5 ft-lbs	9.5 ft-lbs
ENGINE BRAND	Ariens AX	Ariens AX	Ariens AX	Ariens AX	Ariens AX	Ariens AX
STARTING SYSTEM	120V/Recoil	Recoil	120V/Recoil	120V/Recoil	Recoil	Recoil
CLEARING WIDTH	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)
HOUSING HEIGHT	12.2 in (31 cm)	12.2 in (31 cm)	12.2 in (31 cm)	12.2 in (31 cm)	12.1 in (30.7 cm)	12.1 in (30.7 cm)
THROWING DISTANCE	3ft - 25ft (.9 - 7.62M)	3ft - 35ft (.9 - 10.7M)	3ft - 35ft (.9 - 10.7M)	3ft - 35ft (.9 - 10.7M)	3ft - 35ft (.9 - 10.7M)	3ft - 35ft (.9 - 10.7M)
HANDLE TYPE	Ergo	Ergo	Ergo	Ergo		
CHUTE TURNING RADIUS	210°	210°	210°	210°	210°	210°
CHUTE ROTATION	Manual	Manual	Manual	Remote	Manual	Remote
CHUTE CONSTRUCTION	Polymer	Polymer	Polymer	Polymer	Polymer	Polymer
DEFLECTOR CONTROL	Manual	Manual	Manual	Manual	Manual	Manual
TIRE SIZE	7.5 in x 1.75 in (19.1 x 4.4 cm)	7.5 in x 1.75 in (19.1 x 4.4 cm)	7.5 in x 1.75 in (19.1 x 4.4 cm)	7.5 in x 1.75 in (19.1 x 4.4 cm)	7.5 in x 2 in (19.1 cm x 5.1 cm)	7.5 in x 2 in (19.1 cm x 5.1 cm)
AXLE SYSTEM	Solid Unlocked	Solid Unlocked	Solid Unlocked	Solid Unlocked	Solid Unlocked	Solid Unlocked
FUEL TANK CAPACITY	2.9qt (2.7L)	2.9qt (2.7L)	2.9qt (2.7L)	2.9qt (2.7L)	1.5 qt (1.4 L)	1.5 qt (1.4 L)
DRIVE TYPE	Auger Propelled	Auger Propelled	Auger Propelled	Auger Propelled	Auger Propelled	Auger Propelled
SPEEDS: FORWARD AND REV	1 Forward	1 Forward	1 Forward	1 Forward	1 Forward	1 Forward
AUGER DIAMETER	8.375 in (21.3 cm)	8.375 in (21.3 cm)	8.375 in (21.3 cm)	8.375 in (21.3 cm)	8.375 in (21.3 cm)	8.375 in (21.3 cm)
AUGER TYPE	Reinforced Rubber	Reinforced Rubber	Reinforced Rubber	Reinforced Rubber	Reinforced Rubber	Reinforced Rubber
SCRAPER	Polymer Adjustable	Polymer Adjustable	Polymer Adjustable	Polymer Adjustable	Polymer Adjustable	Polymer Adjustable
PRODUCT WARRANTY	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm	3yr Cons, 1yr Comm	3yr Cons, 1yr Comm
FEATURES AT A GLANCE						
HALOGEN HEADLIGHT	No	No	No	No	No	No
HANDWARMERS	No	No	No	No	No	No
SINGLE HAND CONTROL	Yes	Yes	Yes	Yes	Yes	Yes
REMOTE CHUTE ROTATION	No	No	No	Yes	No	Yes
REMOTE DEFLECTOR CONTROL	No	No	No	No	No	No
ELECTRIC START	Yes	No	Yes	Yes	No	No
DRIFT CUTTERS	No	No	No	No	No	No
PACKAGE DIMENSIONS						
LENGTH	35.50 in (90.17 cm)	35.50 in (90.17 cm)	35.50 in (90.17 cm)	35.50 in (90.17 cm)	39.88 in (101.3 cm)	39.88 in (101.3 cm)
WIDTH	23.50 in (59.69 cm)	23.50 in (59.69 cm)	23.50 in (59.69 cm)	23.50 in (59.69 cm)	23.75 in (60.33 cm)	23.75 in (60.33 cm)
HEIGHT	23 in (58.42 cm)	23 in (58.42 cm)	23 in (58.42 cm)	23 in (58.42 cm)	24.63 in (62.56 cm)	24.63 in (62.56 cm)
DRY WEIGHT	107 lb (48.53 kg)	107 lb (48.53 kg)	107 lb (48.53 kg)	107 lb (48.53 kg)	105 lb (47.63 kg)	105 lb (47.63 kg)
ASSEMBLED DIMENSIONS						
LENGTH	35.50 in (90.17 cm)	35.50 in (90.17 cm)	35.50 in (90.17 cm)	35.50 in (90.17 cm)	50.8 in (128.9 cm)	50.8 in (128.9 cm)
WIDTH	23.50 in (59.69 cm)	23.50 in (59.69 cm)	23.50 in (59.69 cm)	23.50 in (59.69 cm)	21.2 in (53.8 cm)	21.2 in (53.8 cm)
HEIGHT	23 in (58.42 cm)	23 in (58.42 cm)	23 in (58.42 cm)	23 in (58.42 cm)	41.7 in (105.9 cm)	41.7 in (105.9 cm)
DRY WEIGHT	107 lb (48.53 kg)	107 lb (48.53 kg)	107 lb (48.53 kg)	107 lb (48.53 kg)	87 lb (39.46 kg)	89 lb (40.37 kg)
AVAILABLE ACCESSORIES	Floor mat, remote chute rotation kit, Sno-Thro cover, high wear paddles	Floor mat, remote chute rotation kit, Sno-Thro cover, high wear paddles	Floor mat, remote chute rotation kit, Sno-Thro cover, high wear paddles	Floor mat, Sno-Thro cover, high wear paddles		

****While Supplies Last! Will be discontinued once engines are used up**



Distribué par / Distributed by :
MTI Canada
Tél. / tel.: 418 839-4127
Français: 1 800 463-4398
English: 1 800 463-7205
Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

Designation Model #	Ariens Power Brush 28 921025	Ariens Power Brush 36 with Hydrostatic Drive 926518	Ariens Power Brush 36 926062
STAGE TYPE	N/A	N/A	N/A
ENGINE POWER	169cc	287cc	265cc
ENGINE BRAND	Subaru EX17	Subaru EX30	Subaru EX27
STARTING SYSTEM	120V/Recoil	12V Key Start	120V/Recoil
CLEARING WIDTH	28 in (71.2 cm)	36 in (91.4 cm)	36 in (91.4 cm)
BRUSH DIAMETER	18" (46 cm)	25" (64 cm)	25" (64 cm)
BRISTLE MATERIAL	Polypropylene	Polypropylene	Polypropylene
BRISTLE LENGTH	6" (15.2 cm)	7" (17.8 cm)	7" (17.8 cm)
BRUSH ROTATION ANGLE	40°	40°	40°
BRUSH ROTATION CONTROL	Remote Trigger	Remote Trigger	Remote Trigger
HANDLEBAR	Regular Handlebar	Commercial Grade Handlebar	Commercial Grade Handlebar
TIRE SIZE	15 in x 5 in (38 x 13 cm)	16 in x 6.5 in (41 x 17 cm)	16 in x 6.5 in (41 x 17 cm)
TIRE TYPE	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread
STEERING	Automatic Traction Control	Automatic Traction Control	Automatic Traction Control
DRIVE TYPE	Disc-O-Matic	Hydrostatic	Disc-O-Matic
SPEEDS	6 Forward/ 2 Reverse	Variable	6 Forward/ 2 Reverse
GEAR CASE	N/A	Cast Aluminum	Cast Aluminum
AUGER DIAMETER	18 in (45.7 cm) Brush	25 in (63.5 cm) Brush	25 in (63.5 cm) Brush
AUGER TYPE	Brush	Brush	Brush
SKID SHOES	N/A	N/A	N/A
SCRAPER BAR	N/A	N/A	N/A
PRODUCT WARRANTY	3 yr Cons, 90 day Comm	3 yr Cons, 1 yr Comm	3 yr Cons, 1 yr Comm
FEATURES AT A GLANCE			
HALOGEN HEADLIGHT	No	Standard	Standard
HANDWARMERS	No	Standard	No
ELECTRIC START	Standard	Standard	Standard
ONE HAND INTERLOCK	Standard	Standard	Standard
PACKAGE DIMENSIONS			
LENGTH	69 in (175.26 cm)	69 in (175.26 cm)	69.50 in (176.53 cm)
WIDTH	49 in (124.46 cm)	49 in (124.46 cm)	50 in (127 cm)
HEIGHT	38 in (96.52 cm)	38 in (96.52 cm)	38.50 in (97.79 cm)
DRY WEIGHT	400 lbs (181.44 kg)	400 lbs (181.44 kg)	450 lbs (204.12 kg)
ASSEMBLED DIMENSIONS			
LENGTH	69 in (175.26 cm)	69 in (175.26 cm)	69.50 in (176.53 cm)
WIDTH	49 in (124.46 cm)	49 in (124.46 cm)	50 in (127 cm)
HEIGHT	38 in (96.52 cm)	38 in (96.52 cm)	38.50 in (97.79 cm)
DRY WEIGHT	400 lbs (181.44 kg)	400 lbs (181.44 kg)	450 lbs (204.12 kg)

**Available while supplies last



ARIENS

Distribué par / Distributed by :

MTI
CANADA

MTI Canada

Tél. / tel.: 418 839-4127
Français: 1 800 463-4398
English: 1 800 463-7205
Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca